



台秤、各种压式测力装置
Platform scale, all kinds of compression testing devices

TECHNICAL PARAMETER

4Wires: Exc+(红, Red); Exc-(黑, Black); Sig+(绿, Green); Sig-(白, White)

额定载荷 Rated capacities(E _{max})	50, 75, 100, 150, 200, 250, 300, 500, 635kg; 1t	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	2.0±0.2mV/V	工作温度范围 Temperature range, operating	-20°C~+50°C
精度等级 Accuracy class	OIML C3(approving)	安全过载 Maximum safe overload	150%E _{max}
蠕变(30分钟) Creep error (30min)	±166ppm	极限过载 Ultimate overload	300%E _{max}
零点平衡 Zero balance	±3%E _{max}	推荐激励电压 Excitation, recommended	10V DC
零点温度影响 TC ZERO	±17.5ppm/°C	最大激励电压 Excitation, maximum	15V DC
输出温度影响 TC SPAN	+20°C~+40°C, ±17.5ppm/°C	防封等级 Protection class	IP65
	-10°C~+20°C, ±11.67ppm/°C	材质 Construction	铝合金 Aluminium
输入阻抗 Input resistance	404 ± 15Ω	电缆 Cable	Length: 6m
输出阻抗 Output resistance	350 ± 3Ω		Diameter: φ 5mm
绝缘电阻 Insulation resistance	≥2000 MΩ (50V DC)	推荐安装力矩 Installation torque, recommended	25N · m
推荐安装台面 Max. platform size	600 × 800mm		