



配料秤、包装秤、动态检测系统、台秤  
Blending scale, packing scale, dynamic testing system, platform scale

## TECHNICAL PARAMETER

4Wires: Exc+(红, Red); Exc-(黑, Black); Sig+(绿, Green); Sig-(白, White)

额定载荷 Rated capacities(E <sub>max</sub> )	200,300,500,750,1000,1500kg	温度补偿范围 Compensated temp range	-10°C~+40°C
灵敏度 Sensitivity	2.0±0.2mV/V	工作温度范围 Operating temp range	-30~+70°C
综合误差 Total error	±0.02%F.S; ±0.03%F.S	安全过载 Safe over load	150%F.S
蠕变 (30分钟) Creep erro (30min)	±0.02%F.S , ±0.03%F.S	极限过载 Ultimate over load	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Recommend excitation	10~12V DC
零点温度影响 TCO	±0.03%F.S/10°C	最大激励电压 Max excitation	15V DC
输出温度影响 TC SPAN	±0.03%F.S/10°C	密封等级 Environmental protection	IP65
输入阻抗 Input impedance	400±20Ω	材质 Material	合金钢 Alloy Steel
输出阻抗 Output impedance	352±3Ω	电缆 Cable	Length:3m
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 5mm