



额定载荷(t) Rated Load	D1	D2	D3	M*P	H1	H2	H3	H4	H5
10	φ 50	φ 40	φ 138	M20*1.5	17	35	74	134.5	20.55
20,25	φ 65	φ 40	φ 165	M24*1.5	25	50	87	161	20.55
30	φ 75	φ 50.8	φ 165	M30*1.5	25	55	86	176	21
40	φ 85	φ 76.2	φ 165	M40*1.5	25	65	95.8	221	25.4

仓储秤、实验机  
warehouse scale, experimental machine

## TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(Emax)	10,20,25,30,40t	温度补偿范围 Temperature range, compensated	-10℃~+40℃
灵敏度 Sensitivity	3.0±0.006mV/V	工作温度范围 Temperature range, operating	-30~+70℃
综合误差 Total error	±0.05%F.S(10~25t); ±0.1%F.S(30~40t)	安全过载 Maximum safe overload	150%F.S;120%F.S(30,40t)
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	200%F.S;150%F.S(30,40t)
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10℃	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10℃	防封等级 Protection class	IP67
输入阻抗 Input impedance	400±20Ω	材质 Construction	合金钢Alloy Steel
输出阻抗 Output impedance	352±3Ω;352±5Ω(L≥15m)	电缆 Cable	Length:12m(10~25t),16m(30~40t)
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 6mm