



量程 (<lb)	D1	D2	D3	D4	SD5	H1	H2	H3	H4	H5	T1
2.5,5,10	104.6	86	21.5	37	19.5	100	20.2	44.3	34.8	25	8xM6
25, 50	122	101.7	25	50	40	147	25	54	47	40	8xM8
60	122	101.7	25	50	40	145.4	25	54	47	40	8xM8
100	138	112	25	50	40	155	30	57	51	40	8xM10



仓储秤、实验机
warehouse scale testing equipment

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(Emax)	5~10,25,50,60,100klb	温度补偿范围 Temperature range, compensated	-10℃~+40℃
灵敏度 Sensitivity	4.0±0.006mV/V	工作温度范围 Temperature range, operating	-30~+70℃
综合误差 Total error	±0.05%F.S;±0.1%F.S (100klb)	安全过载 Maximum safe overload	120%F.S
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	150%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10℃	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10℃	防封等级 Protection class	IP67
输入阻抗 Input impedance	400±20Ω	材质 Construction	合金钢Alloy Steel
输出阻抗 Output impedance	352±3Ω	电缆 Cable	Length:12m
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 6mm