



车载等其它车用传感器,可内置角度模块

Load cells for onboard weighing, ect, built-in module of angular position.

## TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated load	20t	工作温度范围 Operating Temp Range	-30 ~ +70°C
灵敏度 Sensitivity	1.0 ± 0.1mV/V	安全过载 Safe load limit	200%F.S
综合误差 Total error	± 0.5%F.S	极限过载 Lateral load limit	300%F.S
蠕变 (30分钟) Creep(30min)	± 0.1%F.S	推荐激励电压 Recommend excitation	10 ~ 12V DC
零点平衡 Zero balance	± 1%F.S	最大激励电压 Maximum excitation	15V DC
零点温度影响 TCO	± 0.05%F.S/10°C	密封等级 Protection Class	IP67
输出温度影响 TC SPAN	± 0.05%F.S/10°C	材质 Construction	合金钢 Alloy Steel
输入阻抗 Input resistance	750 ± 50 Ω	电缆 Cable	Length: 15m
输出阻抗 Output resistance	702 ± 5 Ω		Diameter: φ6mm
绝缘电阻 Insulation resistance	≥ 5000M Ω		