




压式测力试验设备  
Compression testing equipment

额定载荷(t) Rated Load	L1	L2	H1	H2	H3	H4	D1	D2	D3	Smax
25,30	62	33	192	34	51	15	72	50	37	10.5
40	69	26	225	36	57	16	85	64	37	11
50,60									54.4	12.5
90	69	26	225	36	57	16	85	64	54.4	9

注：Smax为允许的最大侧向位移，推荐侧向位移对于25t取3mm，30-90t取3-5mm。



## TECHNICAL PARAMETER | 4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(Emax)	25,30,40,50,60,90t	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	2.0±0.005mV/V	工作温度范围 Temperature range, operating	-30~+70°C
综合误差 Total error	±0.05%F.S	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10°C	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10°C	防封等级 Protection class	IP67
输入阻抗 Input impedance	400±20Ω	材质 Construction	合金钢Alloy Steel,不锈钢Stainless Steel
输出阻抗 Output impedance	352±5Ω	电缆 Cable Length=L:	10m(25,30t),16m(40,50t),18m(60,90t)
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 8mm