



汽车衡、轨道衡、轴重秤、地上衡
Truck scale, railway scale, axle-load scale, floor scale

TECHNICAL PARAMETER

6Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White);Sen+(蓝,Blue);Sen-(黄,Yellow)

额定载荷 Rated capacities(E _{max})	20,25,30,40,50t	温度补偿范围 Temperature range, compensated	-10℃~+40℃
灵敏度 Sensitivity	2.0±0.003mV/V	工作温度范围 Temperature range, operating	-30~+70℃
综合误差 Total error	±0.03%F.S, ±0.05%F.S	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.02%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation, recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10℃	最大激励电压 Excitation, maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10℃	防封等级 Protection class	IP68
输入阻抗 Input impedance	1160±10Ω	材质 Construction	合金钢 Alloy Steel
输出阻抗 Output impedance	1005±5Ω	电缆 Cable	Length: 12m(20~25t), 14m(30t), 16m(40~50t)
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 6mm