



汽车衡、轨道衡、配料秤及各种专用衡器

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated load	50、60、65、75、100klb	绝缘电阻 Insulation resistance	≥5000 MΩ
精度等级 Accuracy class	0.05	额定温度 Nominal Temp Range	-10~+40℃
灵敏度 Sensitivity	3.0 ± 0.003mV/V	工作温度范围 Service Temp Range	-30~+70℃
线性误差 Non-linearity	±0.05%F.S	安全负载 Safe load limit	150%F.S
滞后误差 Hysteresis error	±0.05%F.S	破坏负载 Breaking load	200%F.S
蠕变 (30分钟) Creep(30min)	±0.03%F.S	额定激励电压 Nominal of range excitation	10~12 V DC
零点温度影响 TC ZERO	±0.02%F.S/10℃	密封等级 Protection Class	IP68
灵敏度温度影响 TC SPAN	±0.02%F.S/10℃	材料 Material	合金钢 Alloy Steel
输入阻抗 Input resistance	750 ± 10Ω	电缆 Cable Length:15.5m	
输出阻抗 Output resistance	702 ± 5Ω		