



多量程实验机
Varied range testing Machines

TECHNICAL PARAMETER | 6Wires: Exc+(红,Red);Exc-(黑,Black);Sig1(信号)+(绿,Green);Sig1(信号)-(白,White);Sig2(信号)+(蓝,Blue);Sig2(信号)-(黄,Yellow)

额定载荷 Rated capacities(Emax)	100/1000kg(双量程 dual capacity)	温度补偿范围 Temperature range, compensated	-10℃~+40℃
灵敏度 Sensitivity	2.0±0.005mV/V	工作温度范围 Temperature range, operating	-30~+70℃
综合误差 Total error	±0.1%F.S	安全过载 Maximum safe overload	120%F.S
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	150%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10℃	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10℃	防封等级 Protection class	IP65
输入阻抗 Input impedance	200±5Ω	材质 Construction	合金钢 Alloy Steel
输出阻抗 Output impedance	352±3Ω	电缆 Cable	Length:6m
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 6mm