


额定载荷 (t) Rated load	L ₁	L ₂	L ₃	H	D ₁	D ₂
2.5	5.5	10	21	31	φ5.5	φ9
10	8	13.5	24.5	33.5	φ6.6	φ10.5



轴重秤
Axle-load scale

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated load	2.5,10t	工作温度范围 Operating Temp Range	-30 ~ +70°C
灵敏度 Sensitivity	1.7 ± 0.01(2 ~ 10t) / 1.6 ± 0.01(3t)mV/V	安全过载 Safe load limit	150%F.S
综合误差 Total error	± 0.3%F.S	极限过载 Lateral load limit	200%F.S
蠕变 (30分钟) Creep(30min)	± 0.1%F.S	推荐激励电压 Recommend excitation	10 ~ 12V DC
零点平衡 Zero balance	± 1%F.S	最大激励电压 Maximum excitation	15V DC
零点温度影响 TCO	± 0.03%F.S/10°C	密封等级 Protection Class	IP65
输出温度影响 TC SPAN	± 0.03%F.S/10°C	材质 Construction	合金钢 Alloy Steel
输入阻抗 Input resistance	750 ± 10Ω	电缆 Cable	Length: 0.5m
输出阻抗 Output resistance	700 ± 2Ω		Diameter: φ5mm
绝缘电阻 Insulation resistance	≥ 5000MΩ		