



配料秤、包装秤、动态检测系统、台秤

Blending scale, packing scale, dynamic testing system, platform scale

TECHNICAL PARAMETER

4Wires: Exc+(红, Red); Exc-(黑, Black); Sig+(绿, Green); Sig-(白, White)

额定载荷 Rated capacities(E _{max})	250,300,500,750,800,1000kg	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	2.0±0.2mV/V	工作温度范围 Temperature range, operating	-30~+70°C
综合误差 Total error	±0.03%F.S(合金钢 alloy steel);0.05%F.S(不锈钢 stainless steel)	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation, recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10°C	最大激励电压 Excitation, maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10°C	防封等级 Protection class	IP65,IP68(-A,-ASS)
输入阻抗 Input impedance	400±20Ω	材质 Construction	合金钢 Alloy Steel 不锈钢 Stainless Steel
输出阻抗 Output impedance	352±3Ω	电缆 Cable	Length:6m
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: Φ 5mm

8-M8孔深20

