



配料秤、包装秤、动态检测系统、台秤

Blending scale, packing scale, dynamic testing system, platform scale

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

| | | | |
|--|-----------------------|---------------------------------------|-----------------------------------|
| 额定载荷 Rated capacities(E _{max}) | 300,600,1000kg,2t | 温度补偿范围 Temperature range, compensated | -10℃~+40℃ |
| 灵敏度 Sensitivity | 2.0±0.2mV/V | 工作温度范围 Temperature range, operating | -30~+70℃ |
| 综合误差 Total error | ±0.03%F.S | 安全过载 Maximum safe overload | 150%F.S |
| 蠕变(30分钟)Creep error (30min) | ±0.02%F.S , ±0.03%F.S | 极限过载 Ultimate overload | 200%F.S |
| 零点平衡 Zero balance | ±1%F.S | 推荐激励电压 Excitation,recommend | 10~12V DC |
| 零点温度影响 TCO | ±0.03%F.S/10℃ | 最大激励电压 Excitation,maximum | 15V DC |
| 输出温度影响 TC SPAN | ±0.03%F.S/10℃ | 防封等级 Protection class | IP65 |
| 输入阻抗 Input impedance | 400±20 Ω | 材质 Construction | 合金钢Alloy Steel 不锈钢Stainless Steel |
| 输出阻抗 Output impedance | 352±3 Ω | 电缆 Cable | Length:3m |
| 绝缘电阻 Insulation impedance | ≥5000M Ω | | Diameter: φ 5mm |