



量程(t)	D	D1	H	H1	H2	H3	L
0.5~1	Φ115	Φ22	43	12	8.4	5	8
2	Φ120	Φ26	45	12	8.4	5	8
3	Φ128	Φ20	46	8	10.4	5	7
5	Φ128	Φ20	46	8	10.4	5	7
10	Φ160	Φ40	63	15	10.4	10	10
15	Φ194	Φ42	68	20	12.4	10	12
20	Φ220	Φ44	73	22	12.4	10	12



料斗秤、仓储秤

Hopper scale, warehouse scale

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated load	0.5,1,2,3,5,10,15,20t	工作温度范围 Operating Temp Range	-30 ~ +70°C
灵敏度 Sensitivity	2.0 ± 0.01mV/V	安全过载 Safe load limit	150%F.S
综合误差 Total error	± 0.05(0.5 ~ 5t) / ± 0.1(10 ~ 20t)%F.S	极限过载 Lateral load limit	200%F.S
蠕变 (30分钟) Creep(30min)	± 0.05%F.S	推荐激励电压 Recommend excitation	10 ~ 12V DC
零点平衡 Zero balance	± 1%F.S	最大激励电压 Maximum excitation	15V DC
零点温度影响 TCO	± 0.02%F.S/10°C	密封等级 Protection Class	IP66(0.5 ~ 5t)
输出温度影响 TC SPAN	± 0.02%F.S/10°C		IP67(10 ~ 20t)
输入阻抗 Input resistance	750 ± 10Ω	材质 Construction	合金钢 Alloy Steel
输出阻抗 Output resistance	702 ± 3Ω	电缆 Cable	Length: 6m
绝缘电阻 Insulation resistance	≥ 5000MΩ		Diameter: φ6mm