



量程	øA	øC	øD ^{+0.1}	øE	øF	G	H	I	J	M
10t	ø164	ø118	ø34 ^{+0.1}	ø52	ø74	15	111	34	30	M30X2
20t	ø190	ø136	ø43 ^{+0.1}	ø67	ø96	22	137	44	40	M39X2



拉压两用、测力机装置

Traction and compression type force testing devices

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(E _{max})	10,20t	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	2.0±0.005mV/V	工作温度范围 Temperature range, operating	-30~+70°C
综合误差 Total error	±0.1%F.S	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10°C	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10°C	防护等级 Protection class	IP67
输入阻抗 Input impedance	400±20 Ω	材质 Construction	合金钢Alloy Steel
输出阻抗 Output impedance	352±3 Ω	电缆 Cable	
绝缘电阻 Insulation impedance	≥5000M Ω		Length: 12m Diameter: φ5mm