



机器人制造、自动化设备、智能机器、材料检测设备。
Robot manufacturing, automation equipment,
intelligent machine, material testing equipment

TECHNICAL PARAMETER

4Wires: Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated load	5t	绝缘电阻 Insulation resistance	≥5 000MΩ
灵敏度 Sensitivity	1.0±0.1mV/V	工作温度范围 Operating Temp Range	-30 ~ +70℃
综合误差 Total error	≥3%F.S	安全过载 Safe load limit	150%F.S
蠕变 (30分钟) Creep(30min)	±0.1%F.S	极限过载 Lateral load limit	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Reccmmend excitation	10 ~ 12V DC
零点温度影响 TCO	±0.1%F.S/10℃	最大激励电压 Maximum excitation	15V DC
输出温度影响 TC SPAN	±0.1%F.S/10℃	密封等级 Protection Class	IP66
输入阻抗 Input resistance	4 00 ± 20Ω	材质 Construction	合金钢 Alloy Steel
输出阻抗 Output resistance	352 ± 3Ω	电缆 Cable	Diameter: φ5mm