



额定载荷(kg) Rated Load	L	L1	L2	L3	L4	H1	H2	A	A1	B	D
2,3	154	104	42	48	8	50	40	15	40	8.5	φ32
5	211	141	63	62	16.8	68	58	20	55	8.5	φ35
10	241	161	64	78	17.3	85	68	25	62	8.75	φ47
15,20	310	202	80	102	20	108	80	35	70	10	φ55
30	351	227	85	118	23	118	85	40	75	10	φ62

吊钩秤、拉式测力装置

Crane scale, tension measuring equipment

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(E _{max})	2,3,5,10,15,20,30t	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	1.8±0.005mV/V	工作温度范围 Temperature range, operating	-30~+70°C
综合误差 Total error	±0.05%F.S	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10°C	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10°C	防封等级 Protection class	IP67
输入阻抗 Input impedance	400±20Ω	材质 Construction	合金钢Alloy Steel
输出阻抗 Output impedance	352±3Ω;352±5Ω(L≥15m)	电缆 Cable	Length=L:2m(2~5t),16m(10~15t),20m(20~30t)
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 5mm