



静态扭矩测试、扭矩扳手检测等场合

Static torque test, torque wrench test etc.

## TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(E <sub>max</sub> )	50,100N.m	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	1.0~2.0mV/V	工作温度范围 Temperature range, operating	-30~+70°C
综合误差 Total error	±0.5; ±1%F.S	安全过载 Maximum safe overload	120%F.S
蠕变(30分钟)Creep error (30min)	±0.05%F.S	极限过载 Ultimate overload	180%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation, recommend	10~12V DC
零点温度影响 TCO	±0.03%F.S/10°C	最大激励电压 Excitation, maximum	15V DC
输出温度影响 TC SPAN	±0.03%F.S/10°C	防护等级 Protection class	IP66
输入阻抗 Input impedance	400 ± 20 Ω	材质 Construction	合金钢 Alloy Steel
输出阻抗 Output impedance	352 ± 3 Ω	电缆 Cable	
绝缘电阻 Insulation impedance	≥5000M Ω		

Length: 5m

Diameter: φ5mm