


参数	量程(t)				
	15	20	25	30	
				常规30t压头	常规40t压头
A (mm)	198.7			202.7	
B (mm)	42			46	



汽车衡、轴重秤、仓储秤等

Truck scale, axle-load scale, warehouse scale

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated load	15,20,25,30t	绝缘电阻 Insulation resistance	≥500MΩ
灵敏度 Sensitivity	2.0 ± 0.002mV/V	工作温度范围 Operating Temp Range	-30 ~ +70℃
综合误差 Total error	± 0.035%F.S	安全过载 Safe load limit	150%F.S
蠕变 (30分钟) Creep(30min)	± 0.02%F.S	极限过载 Lateral load limit	200%F.S
零点平衡 Zero balance	± 1%F.S	推荐激励电压 Recommend excitation	10 ~ 12V DC
零点温度影响 TCO	± 0.02%F.S/10℃	最大激励电压 Maximum excitation	15V DC
输出温度影响 TC SPAN	± 0.02%F.S/10℃	密封等级 Protection Class	IP68
输入阻抗 Input resistance	750 ± 10Ω	材质 Construction	合金钢 Alloy Steel
输出阻抗 Output resistance	703 ± 2Ω	电缆 Cable	Diameter: φ6mm