



额定载荷(t) Rated Load	A	B	C	D	E	F	H	L	J	K
0.1~0.3	135	36	26	18	75	25	32	58	11.5	11.5
0.5~2	135	38	30	18	75	25	34	58	13.5	13.5
3~5	170	48	38	20	85	50	39	79	18	18.5
10	263	60	60	30	118	90	52	143	26	26

TECHNICAL PARAMETER | 4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(E _{max})	0.1,0.2,0.3,0.5,1,2,3,5,10t	温度补偿范围 Temperature range, compensated	-10℃~+40℃
灵敏度 Sensitivity	2.0±0.002mV/V	工作温度范围 Temperature range, operating	-30℃~+70℃
综合误差 Total error	0.1~2t: ±0.03%F.S.;3~5t: ±0.05%F.S; 10t:0.1%F.S.(合金钢产品Alloy Steel Product)		
	0.1~3t: ±0.05%F.S.;5t:0.1%F.S; 10t:0.2%F.S.(不锈钢产品Stainless Steel Product)	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.02%F.S ; ±0.05%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10℃	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10℃	防封等级 Protection class	IP66(0.1~0.5t),IP67(1~10t)
输入阻抗 Input impedance	400±20Ω	材质 Construction	合金钢Alloy Steel
输出阻抗 Output impedance	352±3Ω	电缆 Cable	
绝缘电阻 Insulation impedance	≥5000MΩ		Length:3m(0.1~0.5t),5m(1~5t);8m(10t) Diameter: φ 5mm(0.1~5t); φ 6mm(10t)