



地上衡、配料秤、平面台秤

Floor scale, blending scale, platform scale

额定载荷(t) Rated Load	L	L1	L2	L3	L4	A	B	C	D	H	H1	H2
0.5,1,2	132	14.7	76.2	25.4	56.5	32	M12	φ 13.8	φ 13.5	33.5	31.5	15.7
3,5	171.5	19	95.3	38.1	76.2	38	M18x15	φ 20	φ 20	44.5	38	26

TECHNICAL PARAMETER | 4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(Emax)	0.5,1,2,3,5t	温度补偿范围 Temperature range, compensated	-10℃~+40℃
灵敏度 Sensitivity	2.0±0.002mV/V	工作温度范围 Temperature range, operating	-30~+70℃
综合误差 Total error	±0.03%F.S; ±0.05%F.S	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10℃	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10℃	防封等级 Protection class	IP67(0.5t);IP68(1~5t)
输入阻抗 Input impedance	400±20Ω	材质 Construction	合金钢Alloy Steel
输出阻抗 Output impedance	352±2Ω	电缆 Cable	Length:3m(0.5~2t),5m(3t),6m(5t)
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 5mm