



额定载荷(t) Rated Load	L	L1	L2	L3	L4	H/B	D1	D2
0.5,0.75,1,1.5,2,2.5	130	12.7	76.2	25.4	53.5	31.8	M12	φ 13
3,5	171.5	19	95.3	38.1	72.5	38.1	M18x15	φ 20

配料秤、平面台秤  
blending scale, platform scale

## TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(E <sub>max</sub> )	0.5,0.75,1,1.5,2,2.5,3,5t	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	3.0±0.003mV/V	工作温度范围 Temperature range, operating	-30~+70°C
综合误差 Total error	±0.03%F.S(合金钢Alloy Steel); ±0.05%F.S(不锈钢Stainless Steel)	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.03%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.02%F.S/10°C	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.02%F.S/10°C	防封等级 Protection class	IP66(0.5~0.75t);IP67(1~5t)
输入阻抗 Input impedance	400±20Ω	材质 Construction	合金钢Alloy Steel 不锈钢Stainless Steel
输出阻抗 Output impedance	352±3Ω	电缆 Cable	Length: 3m(0.5~2.5t),4.2m(3~5t)
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 6mm