



配料秤、包装秤、动态检测系统、台秤
Blending scale, packing scale, dynamic testing system, platform scale

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

| | | | |
|-----------------------------|--------------------------------------------------------------------|----------------------------------------|------------------------------|
| 额定载荷 Rated capacities(Emax) | 50,100,200,300,500,600,635,1000kg; 100,250,500,750,1000,2000lb; | 温度补偿范围 Temperature range, compensated | -10℃~+40℃ |
| 灵敏度 Sensitivity | 2.0±0.2mV/V | 工作温度范围 Temperature range, operating | -20℃~+50℃ |
| 精度等级 Accuracy class | OIML C3(approving) | 安全过载 Maximum safe overload | 150%Emax |
| 蠕变(30分钟)Creep error (30min) | ±166ppm | 极限过载 Ultimate overload | 300%Emax |
| 零点平衡 Zero balance | ±3%Emax | 推荐激励电压 Excitation,recommended | 10V DC |
| 零点温度影响 TC ZERO | ±17.5ppm/℃ | 最大激励电压 Excitation,maximum | 15V DC |
| 输出温度影响 TC SPAN | +20℃~+40℃, ±17.5ppm/℃ -10℃~+20℃, ±11.67ppm/℃ | 防封等级 Protection class | IP65 |
| 输入阻抗 Input resistance | 404±15Ω | 材质 Construction | 铝合金Aluminium |
| 输出阻抗 Output resistance | 350±3Ω | 电缆Cable | Length:3m Diameter: φ 5mm |
| 绝缘电阻 Insulation resistance | ≥2000 MΩ (50V DC) | 推荐安装力矩 Installation torque,recommended | 25N·m |
| 推荐安装台面 Max. platform size | 600×800mm | | |