



各种拉压场合、内置式测力专用设备

Tebstion testing for pull/push & special device

## TECHNICAL PARAMETER

4Wires:Exc+(红,Red); Sig+(绿,Green); Sig-(白,White); Exc-(黑,Black)

额定载荷 Rated capacities(Emax)	1,2,3,5,10,20,50,100kg (XSG)	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	0.5 ± 0.1mV/V(1kg)	工作温度范围 Temperature range, operating	-30~+70°C
	1.0 ± 0.2mV/V(1kg)	安全过载 Maximum safe overload	120%F.S
综合误差 Total error	±0.2%F.S	极限过载 Ultimate overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.2%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点平衡 Zero balance	±1%F.S	最大激励电压 Excitation,maximum	15V DC
零点温度影响 TCO	±0.2%F.S/10°C	防封等级 Protection class	IP65
输出温度影响 TC SPAN	±0.2%F.S/10°C	材质 Construction	铝合金Aluminium(XSCB);合金钢Alloy Steel(XSGB)
输入阻抗 Input impedance	350 ± 5 Ω	电缆 Cable	
输出阻抗 Output impedance	350 ± 5 Ω		Length:25cm(排线)
绝缘电阻 Insulation impedance	≥5000M Ω		