



轮轴识别器
Axle wheel identify unit

TECHNICAL PARAMETER

4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

额定载荷 Rated capacities(Emax)	1,2t	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	2.0±0.1mV/V	工作温度范围 Temperature range, operating	-30~+70°C
综合误差 Total error	±0.5%F.S	安全过载 Maximum safe overload	120 %F.S
蠕变(30分钟)Creep error (30min)	±0.5%F.S	极限过载 Ultimate overload	150 %F.S
零点平衡 Zero balance	±2%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.2%F.S/10°C	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.2%F.S/10°C	防封等级 Protection class	IP67
输入阻抗 Input impedance	900±30Ω	材质 Construction	合金钢Alloy Steel
输出阻抗 Output impedance	700±5Ω	电缆 Cable	Length:4.5m (2t) 10m(1t)
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 5mm