



拉压测试场合、试验机  
Tension testing situation, testing machine

量程(t)	H	H1	D	D1	NX φD2	α
40,60	160	25	197	160	12x φ 22	15°
100	230	40	240	200	12x φ 26	15°
150~200	326	57	305	250	12x φ 32	15°
300	358	69	415	360	18x φ 33	10°

## TECHNICAL PARAMETER

6Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White);Sen+(蓝,Blue);Sen-(黄,Yellow)

额定载荷 Rated capacities(Emax)	40,50,60,100,150,200,300t	温度补偿范围 Temperature range, compensated	-10°C~+40°C
灵敏度 Sensitivity	2.0±0.01mV/V	工作温度范围 Temperature range, operating	-30~+70°C
综合误差 Total error	±0.3%F.S	安全过载 Maximum safe overload	150%F.S
蠕变(30分钟)Creep error (30min)	±0.05%F.S	极限过载 Ultimate overload	200%F.S
零点平衡 Zero balance	±1%F.S	推荐激励电压 Excitation,recommend	10~12V DC
零点温度影响 TCO	±0.03%F.S/10°C	最大激励电压 Excitation,maximum	15V DC
输出温度影响 TC SPAN	±0.03%F.S/10°C	防封等级 Protection class	IP67
输入阻抗 Input impedance	750±10Ω	材质 Construction	合金钢Alloy Steel
输出阻抗 Output impedance	702±3Ω ;702±5Ω (C≥15m)	电缆 Cable	Length:14m(40~100t),20m(150~300t)
绝缘电阻 Insulation impedance	≥5000MΩ		Diameter: φ 8mm