



| 尺寸<br>(mm) | 尺寸<br>(mm) |      |       |       |      |      |      |      |
|------------|------------|------|-------|-------|------|------|------|------|
|            | A          | B    | C     | D     | E    | F    | G    | H    |
| 2~5        | 31         | 31   | 190.5 | 159.1 | 12.7 | 30.5 | 31.5 | 14.2 |
| 10~35      | 36.6       | 48.5 | 222   | 190.5 | 19   | 42   | 50.6 | B/2  |
| 50~75      | 62         | 74.7 | 342.9 | 292.1 | 33.5 | 82.6 | 75.9 | B/2  |

汽车衡、地上衡、仓储秤等  
Truck scale, floor scale, warehouse scale

## TECHNICAL PARAMETER | 4Wires:Exc+(红,Red);Exc-(黑,Black);Sig+(绿,Green);Sig-(白,White)

|  |   |                                       |  |
|--|---|---------------------------------------|--|
| 额定载荷 Rated capacities(E <sub>max</sub> ) | 2,2.5,3.5,10,25,35,50,75klb                         | 温度补偿范围 Temperature range, compensated | -10°C~+40°C                              |
| 灵敏度 Sensitivity                          | 3.0±0.005mV/V                                       | 工作温度范围 Temperature range, operating   | -30~+70°C                                |
| 综合误差 Total error                         | ±0.03%F.S; ±0.05%F.S; ±0.1%F.S (不锈钢Stainless Steel) | 安全过载 Maximum safe overload            | 150%F.S                                  |
| 蠕变(30分钟)Creep error (30min)              | ±0.02%F.S   | 极限过载 Ultimate overload                | 200%F.S                                  |
| 零点平衡 Zero balance                        | ±1%F.S  | 推荐激励电压 Excitation, recommend          | 10~12V DC                                |
| 零点温度影响 TCO                               | ±0.02%F.S/10°C                                      | 最大激励电压 Excitation, maximum            | 15V DC                                   |
| 输出温度影响 TC SPAN                           | ±0.02%F.S/10°C                                      | 防封等级 Protection class                 | IP68                                     |
| 输入阻抗 Input impedance                     | 750±10Ω   | 材质 Construction                       | 合金钢Alloy Steel 不锈钢Stainless Steel        |
| 输出阻抗 Output impedance                    | 702±3Ω  | 电缆 Cable                              | Length=6m(2~5klb), 10m(10~35klb)         |
| 绝缘电阻 Insulation impedance                | ≥5000MΩ   |                                       | Diameter: φ 5mm(2~5klb), φ 6mm(10~35klb) |